



### WB-BB-LP-300-1

JOB: \_\_\_\_\_ ITEM: \_\_\_\_\_

#### LOW PROFILE 1/3 HP GLYCOL LINE CHILLER WITH ONE PUMP

- REFRIGERATION:** Air-Cooled: 1/3 HP, R134a Condensing Unit  
2000 BTU Output
- NOTE:** 12" clearance required on on sides for optimum air flow maintenance.
- ELECTRICAL:** 115 Volt AC, 60 hZ, 1 phase, 14.0 Full Load Amps  
Dedicated 20 Amp circuit is required  
Maximum Fuse / HACR Breaker: 20 Amp  
Includes six-foot cord with NEMA 5-20P grounded plug.
- RECIRCULATING PUMP:** One 100 GPH, Brass Recirculation Duty
- RECIRCULATING MOTOR:** 1/3 hp (6.2 Amp)
- DIMENSIONS:** Height: 15"  
Width: 22-3/4"  
Depth: 24-1/4"
- WEIGHT:** Shipping: 225#  
Operating: 250#
- COOLANT CAPACITY:** 6 U.S. Gallons \*\*  
(3 gallons glycol plus 3 gallons water)
- MAXIMUM CONDUIT LENGTH:** 175'
- OPTIONS:** 6" Adjustable Legs (up to 7")  
Additional Recirculating Pump and Motor Kit



\*\* Add one gallon of coolant mixture (50% glycol plus 50% water) per 100 feet of Conduit



**Includes:**  
Six-foot long  
cord with  
NEMA 5-20P,  
grounded plug.

